

**Dynaudio quality, tailored for you.**

Dynaudio Custom Performance in-wall speakers are super-shallow for tight cavities, and are optimised for wide dispersion.

# Performance series

## In-wall






**DYNAUDIO**

# Performance series

## In-wall

- 2-way systems
- Ranging from 6.5 Inch to 8 Inch.
- EQ Adjustments for the tweeter
- Magnetic paintable Grille
- Shallow speakers with high performance
- MSP woofer cone
- 1" Silk dome

| Model number / in-ceiling                | P4-W65  | P4-W80  | P4-LCR50  |
|--|---|---|---|
|  |  |  |  |
| Type                                     | 2-way in-wall   | 2-way in-wall   | 2-way in-wall mid/tweeter module  |
| Drivers                                  | Tweeter: 28mm (1in); mid/bass: 165mm (6½in)                                       | Tweeter: 28mm (1in); mid/bass: 200mm (8in)  | Tweeter: 28mm (1in); mid/bass: 2x130mm (5in)  |
| Performance frequency response (+/- 3dB) | 55Hz–20kHz  | 45Hz–20kHz  | 70Hz–20kHz  |
| Impedance (nominal/minimum)              | 8Ω / 5Ω   | 8Ω / 5Ω   | 8Ω / 5Ω   |
| Sensitivity (dB SPL [2.83V/1m])          | 87.5dB  | 89.0dB  | 89±3dB (250-20KHz)  |
| Rated power*                             | 50W   | 60W   | 50W   |
| Long term power*                         | 100W  | 100W  | 100W  |
| Tweeter level options                    | -3dB, 0dB +3dB  | -3dB, 0dB +3dB  | +3dB, 0dB, -3dB   |
| Dimensions (W x H x D)                   | 198 x 296mm x 63mm<br>(7¾ x 11½in x 2½in)   | 237 x 392mm x 77mm<br>(9⅝ x 15⅜in x 3in)  | 360 x 195mm x 77mm<br>(14¼in x 7¾in x 3in)  |
| Cut-out dimensions                       | 175 x 275mm<br>(6⅞ x 10⅜in)   | 215 x 370mm<br>(8½ x 14⅞in)   | 175 x 340mm<br>(6⅞in x 13⅜in)   |
| Grille material                          | Painted steel   | Painted steel   | Painted steel   |
| Grille options                           | Rectangular   | Rectangular   | Rectangular   |
| Grille attachment                        | Magnetic  | Magnetic  | Magnetic  |
| Grille finish                            | White (paintable)   | White (paintable)   | White (paintable)   |
| Certifications                           | CE  | CE  | CE  |
| Environmental                            | RoHS  | RoHS  | RoHS  |

\* Power handling according to IEC268. Rated power is continuous power for 100 hours.