





Features

- 4 Channel Power Amplifier
- 4 x 70W Class AB amplification (all channels driven)
- Toroidal transformer
- Ethernet, RS232 control

Exceptional Power, Immersive Sound

The PA410 is a high-performance power amplifier that delivers 4 channels of efficient Class AB amplification. With an impressive 70W per channel, the PA410 is designed to offer the greatest flexibility and power without compromising on control.

Featuring the best-in-class components including a toroidal based power supply, acoustically damped chassis, paralleled transistor output stages and exceptionally low levels of distortion, the PA410 masters the reproduction of music with all its originality and detail for an unmatched level of sound quality and clarity.



Continuous power output at 0.2% THD per channel	
Four channels driven, 4Ω / 8Ω , 20Hz – 20kHz	70W / 50W
Two channels driven, 4 Ω / 8 Ω , 20Hz – 20kHz	90W / 60W
Harmonic distortion, 80% power, 8 Ω at 1kHz	0.003%
Inputs	
Input sensitivity 50W / 8Ω	600mV RMS
Signal/Noise ratio (A-wtd) 50W / 8Ω	105dB
Input impedance	10kΩ
Frequency response	20 - 20kHz +/-0.05dB
General	
Mains voltage	110–120V or 220–240V, 50–60Hz
Power consumption (maximum)	700W
Power consumption (idle, typical)	90W (Thermal dissipation approx. 340 BTU/hour)
Power consumption (standby)	<0.5W
Dimensions W x H x D (including feet, control knob and speaker terminals)	433x325x105mm
Weight (net)	10kg
Weight (packed)	11.5kg
EAN	6925281969195



© 2019 HARMAN International Industries, Incorporated. All rights reserved. Arcam is a registered trademark of HARMAN International Industries, Incorporated registered in the United States and/or other countries. Features, specifications, and appearance are subject to change without notice.