



T/7x



SUGGESTED RETAIL: £999

T/7x is the perfect answer for the real world. It's compact enough (and beautiful enough) to end arguments before they begin; while powerful enough to easily answer most needs and balanced enough to blend beautifully with many of the quality speakers out there and still flexible enough to work in specialty applications.

Specifications

TYPE	Front-firing active driver, down-firing passive
ACTIVE DRIVER SIZE & MATERIAL	8 in., 200mm long-throw, FibreAlloy™ inverted aluminium dust cap, steel chassis
PASSIVE RADIATOR SIZE & MATERIAL	10 in., 254mm long-throw, inverted dust cap
LOW FREQUENCY EXTENTION	-6dB at 30 Hz
INPUT CONNECTORS	High Level Neutrik Speakon, Low Level single RCA, LFE RCA
OUTPUT CONNECTORS	N/A
POWER OUTPUT	200 Watts (RMS)
AMPLIFIER TYPE	Class A/B
WIRELESS CAPABILITY	Arrow (Optional), Zero Compression, Single Large Scale Integrated Chip



TOP

Protection System



FULLY ELECTRONIC SET SAFE	Yes
D.C. FAULT	Yes
OUTPUT SHORT	Yes
MAINS INPUT VOLTAGE	220-240 volts, 110-120 volts for certain markets
FUSES	2 Amp semi delay 230 volts operation, 4 Amp semi delay 115 volts operation

Dimensions

W X H X D	14.0 x 12.6 x 14.3 in., (356 x 320 x 363 mm)
NET WEIGHT	38.5 lbs. (17.5 kg)
FINISH	High Gloss Black, High Gloss White, 5 coats

Supplied Accessories

MAINS LEAD	Yes
NEUTRIK SPEAKON	Yes (10 Meters Nominal)
INTERCONNECT	
USERS MANUAL	Yes



TOP