



T/9x



SUGGESTED RETAIL: £1,299


Serie T/x is instantly seen as crisper, fresher, a full upgrade . Our goals were not simply to improve upon its illustrious predecessor, but to deliver as much as possible of our latest Serie S on a budget. Faster, more transparent sounding system performance awaits you with higher output levels and even greater impact.

Specifications

TYPE	Front-firing active driver, down-firing passive
ACTIVE DRIVER SIZE & MATERIAL	10 in. FibreAlloy™, 254mm long-throw, inverted alloy dust cap, steel chassis
PASSIVE RADIATOR SIZE & MATERIAL	10 in., 254mm long throw, inverted dust cap
LOW FREQUENCY EXTENTION	-6dB at 27 Hz
INPUT CONNECTORS	High Level Neutrik Speakon, Low Level single RCA, LFE RCA
OUTPUT CONNECTORS	N/A
POWER OUTPUT	300 watts (RMS)
AMPLIFIER TYPE	Class A/B
WIRELESS CAPABILITY	Arrow (Optional), Zero Compression Single Large Scale Integrated Chip

Protection System



FULLY ELECTRONIC SET SAFE	Yes	
D.C. FAULT	Yes	
OUTPUT SHORT	Yes	
MAINS INPUT VOLTAGE	220-240 volts, 110-120 volts for certain markets	
FUSES	3.15 Amp semi delay 230 volts operation, 6.3 Amp semi delay 115 volts operation	

Dimensions

W X H X D	14.5 x 13.4 x 15.5 in., (370 x 340 x 393 mm)
NET WEIGHT	45.5 lbs. (20.6 kg)
FINISH	High Gloss Black, High Gloss White, 5 coats

Supplied Accessories

MAINS LEAD	Yes
NEUTRIK SPEAKON	Yes (10 Meters Nominal)
INTERCONNECT	
USERS MANUAL	Yes

