



LYNGDORF MP-40 2.1

SURROUND SOUND PROCESSOR

The MP-40 2.1 multichannel processor from Lyngdorf Audio offers the same sonic qualities and performance of the flagship processor, the MP-60 2.1, in a streamlined design for smaller immersive or surround sound home cinemas where less decoding channels are required. The MP-40 2.1 features 12 native channel decoding and 16 balanced audio outputs and offers full support of the immersive surround formats DOLBY ATMOS®, DTS:X® and AURO-3D®. Ease of installation and user-friendly features are complemented with a simplified feature allowing the chance for one to experience the performance that Lyngdorf Audio is famous for without all the bells and whistles.

STATE-OF-THE-ART HDMI PROCESSING

With three HDMI inputs and two outputs, the MP-40 supports HDMI 2.1 including eARC, Dynamic Lip-Sync and QMS (Quick Media Switching) as well as the latest decoding and post-processing formats. It supports 40 Gbps fixed rate link (FRL) and 18 Gbps transition minimized differential signaling (TMDS) video rates, Variable refresh rate (VRR), Quick Frame Transport (or Fast Vactive), and auto low latency mode (ALLM) support and high dynamic range (HDR) metadata passthrough for HDMI dynamic HDR, HDR10+, and Dolby Vision™.

eARC will allow for a full Dolby Atmos audio bitstream being returned to the processor from the television, ensuring full audio quality from the TV's built-in media players.

BUILT-IN MEDIA PLAYER

The MP-40 features a built-in media player, which connects to services like Spotify, Airplay, UPnP, and Roon as well as internet radio. Through a cabled network or USB connector, you can access your music library and enjoy it in stereo or as up-mixed on a surround sound format.

ROOMPERFECT™ ROOM CORRECTION

The MP-40 2.1 is equipped with Lyngdorf Audio's proprietary RoomPerfect™ calibration technology, the world's most sophisticated technology for adapting the sound system to the environment. The RoomPerfect™ calibration ensures a perfect surround sound experience in nearly any installation environment reducing or even eliminating bulky bass traps and other expensive acoustic treatment.

With RoomPerfect™ it is for the first time possible to obtain seamless level alignment where you experience a lifelike sound scenery instead of individual loudspeakers. Together with a bass management that works due to the true integration of main speakers and subwoofers. This gives much more freedom when choosing speakers and their placement and, perhaps even more important, guaranteed performance – every time.

DEAD SILENT

The MP-40 has no forced cooling, so you will never hear any noisy fans. If used with the Lyngdorf SDA-2400 power amplifier, which don't have fans either, you will have a dead silent system, where you can enjoy everything from the faintest details to the loudest bangs with full dynamics and realism.

CUSTOM VOICINGS

The built-in voicing tool will allow you to customize up to 32 voicings. This allows you to cater to your personal preferences by changing the overall tonality of the system and dedicating voicings to each input of the MP-40. The voicing tool can also be used to compensate for a poor sounding recording. Each unique voicing can consist of up to eight filters with adjustable frequency, gain and Q, all controlled through the browser interface showing the effect of each filter as well as the overall effect to the tonality.



SPECIFICATIONS

Description:	Surround sound processor
Decoding:	12 decoding/upmixing channels, Dolby Atmos®, DTS:X, AURO-3D®, all legacy codecs
Post processing options:	Dolby Surround, AURO-MATIC®, DTS Neural:X
Audio inputs:	3 x HDMI ($\leq 192\text{kHz}/24\text{bit}$), 1 x HDMI eARC, 1 x AES/EBU S/P-DIF input ($\leq 192\text{kHz}/24\text{bit}$), 3 x S/P-DIF coaxial inputs ($\leq 192\text{kHz}/24\text{bit}$), 4 x S/P-DIF optical inputs ($\leq 96\text{kHz}/24\text{bit}$), 1 x USB audio input ($\leq 192\text{kHz}/32\text{bit}$), 1 x microphone input (XLR) for RoomPerfect™
Audio outputs:	16 x XLR analog outputs (16 Vrms), 1 x SPDIF coax digital ZONE output (Fix 96kHz/24bit)
Audio specifications:	Frequency response: $\pm 0,5\text{dB}$ from 20 to 20,000 Hz, Total harmonic distortion: 0.005% max from 20 to 20,000 Hz
EQ:	RoomPerfect™, subwoofer level assistant, 32 x adjustable voicings holding ≤ 8 shelving, high/low pass or parametric filters with adjustable frequency, gain and Q
Media player:	Internet radio (vTuner), Airplay, Spotify Connect, Roon Endpoint, DLNA Support of FAT32 based media storage
Video inputs:	3 x HDMI 2.1 (HDCP 2.3), accepts 8k30 RGB/YCbCr 4:4:4 10-bit video, 8k60 YCbCr 4:2:0 10-bit high definition video, 4k120 4:4:4 10-bit high frame rate video, variable refresh rate (VRR), fast vactive (FVA), and auto low latency mode (ALLM) support, accepts HDR, Dolby Vision™ and HLG
Video outputs:	2 x HDMI 2.1 (HDCP 2.3)
Control interfaces:	1 x DB9 RS232 connector, 2 x IR sensor inputs, 1 x IR output (loop from one of the sensor inputs), 1 x trigger input, 4 x trigger outputs, 1 x RJ45 ethernet LAN connector, 2 x USB A connectors, 1 x SD card slot, (Backup - storage for system software and settings)
Accessories included:	RoomPerfect™ microphone, microphone stand, microphone cable, RF remote control
Placement options:	Rack mount or freestanding
Heat dissipation value:	290 BTU
Dimensions (H x W x D):	140 x 450 x 359 mm 5.51 x 17.7 x 14.1 inches
Weight:	6.7 kg / 14.8 lb
Finish:	Matte black
Item no.:	900010499