



Bowers & Wilkins

HTM71 S3 Signature

Technical Information



Technical Features

Decoupled Carbon Dome tweeter
Solid Body Tweeter-on-Top
Continuum™ cone FST midrange
Aerofoil™ Profile bass cones
Flowport™

Description

3-way vented-box system

Drive Units

1x ø25mm (1 in) Decoupled Carbon Dome high-frequency
1x ø130mm (5 in) Continuum cone FST midrange
2x ø130mm (5 in) Aerofoil Profile bass

Frequency Range

-6dB 45Hz - 33kHz

Frequency Response (+/-3dB from reference axis)

50Hz - 28kHz ±3dB

Sensitivity (on axis at 2.83Vrms at 1m)

89dB

Harmonic Distortion

2nd and 3rd harmonics (90dB, 1m on axis)
<1% 90Hz - 22kHz
<0.5% 120Hz - 20kHz

Nominal Impedance

8Ω (minimum 3.0Ω)

Recommended Amplifier Power

30W - 200W into 8Ω on unclipped programme

Max. Recommended Cable Impedance

0.1Ω

Dimensions

Height: 165 mm (6.5 in) cabinet only
233 mm (9.2 in) including tweeter
Width: 628 mm (24.7 in) cabinet only
Depth: 318 mm (12.5 in) cabinet only
356 mm (14.0 in) including grille and terminals

Net Weight

19.9 kg (43.9 lbs)

Finishes

Cabinet: Datuk Gloss
Midnight Blue Metallic
Grille: Black